

DENSO FIBER-WRAP

Fiber-Mesh Fabric Outerwrap Used Over Petrolatum Tape Systems

Description

Denso Fiber-Wrap is a resin coated, woven fiber-mesh fabric that is .005 inches in thickness and exhibits excellent tensile strength.

Uses

Used as an outerwrap for Denso Petrolatum Tape Systems for straight pipe. Provides additional protection against backfill and soil stress.

Features

- Excellent tensile strength
- Superior holding force
- Provides protection against backfill
- Provides protection against soil stresses

Application

The Denso Fiber-Wrap shall be spirally wrapped using sufficient tension to wrap over the Denso Petrolatum Tape. Apply using a minimum 1" overlap while pressing firmly onto the Denso Petrolatum Tape.



Denso Fiber-Wrap

Property Specifications

PROPERTIES	VALUES
Tensile Strength (per 1 inch width)	85 lb. min.
Thread Count per Inch:	
Warp Threads	20
Fill Threads	10
Thickness	.005 inches
Color	White
Roll Width	4", 6", and 12"
Roll Length	150 ft

Quantity Estimates

Tape Width	Rolls/ Case	Coverage with 1" Overlap	Coverage with 55% Overlap
4"	6	225 ft ² /case	150 ft ² /case
6"	4	250 ft ² /case	150 ft ² /case
12"	2	825 ft ² /case	150 ft ² /case

** All rolls are 150 feet in length.*



DENSO NORTH AMERICA

HOUSTON:
9747 Whithorn Drive,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.