

DENSO® ROAD MAINTENANCE PRODUCTS

BITUMINOUS TAPES & PRIMERS FOR THE SEALING AND WATERPROOFING OF ROAD SURFACES AND PAVEMENTS

PRODUCTS IN THE RANGE:

DensoBand™

Denso Re-instatement Tape $^{\mathsf{TM}}$

Denso Butyl Spray Primer[™]

Denso Primer D™











DENSOBAND™

A polymer modified bitumen strip for sealing cold joints with hot asphalt to asphalt, concrete or steel in road repair or construction.

DensoBand[™] forms a flexible watertight seal which allows for road movement from traffic load and thermal changes thereby preventing cracking and the subsequent failure of the joint.

BENEFITS & USES

- Used in road, parking lot, railway crossing and airport runway repair and construction.
- Sealing bridge decks and flyover expansion joints.
- Minimizes return maintenance visits.
- Uniform flexible seal for joints.
- Adheres to asphalt, concrete, steel and other surfaces.
- Withstands road movement from traffic load and thermal changes.
- Over 30 years of proven history.
- Accepted by many municipalities.

PRIMERS

DENSO PRIMER D™

A specially formulated primer for preparing the surface of concrete, asphalt or steel for the application and good adhesion of Denso road maintenance products.

Both Denso Primer D and Denso Butyl Spray Primer can be used with either DensoBand or Denso Re-instatement Tape.



SYSTEM FEATURES:

- Prevents water ingress in new and existing joints between asphalt, concrete and steel.
- Creates a tough, durable seal and reduces the need for return maintenance visits.
- Fast installation for minimal road closure time.
- Hot and cold applied systems.
- Specially formulated primers to encourage good adhesion of products to joint surfaces.





DENSO RE-INSTATEMENT TAPE™

A cold applied, polymer modified bituminous sealing strip that is applied vertically to create a tough, uniform, waterproof seal. For sealing joints between existing asphalt and new asphalt installations. Used in conjunction with primer. Adheres to asphalt, concrete and steel.

BENEFITS & USES

- Instantly seals against water ingress, preventing cracking and fretting.
- Traffic can pass over immediately.
- Elastic properties accommodate thermal movement.
- Fast installation.
- Proven effective on asphalt, concrete and steel.



DENSO BUTYL SPRAY PRIMER IS EASILY APPLIED TO THE VERTICAL JOINT FACE

DENSO BUTYL SPRAY PRIMER™

Denso Butyl Spray PrimerTM is easily applied to quickly provide an adhesive to hold the appropriate Denso asphalt tape in place until the installation of the top lift of hot mix asphalt. Convenient and portable, Denso Butyl Spray Primer can be used when the substrate is clean but cold, to ensure good adhesion prior to the asphalt placement.

One can is expected to cover approximately 230 LF (70 linear meters) per hour allowing for quick installation of DensoBand and Denso Reinstatement Tape to cold joints of many sorts including asphalt, steel and concrete thereby protecting new asphalt joints from the destructive power of water and ice.

DENSO® ROAD MAINTENANCE PRODUCT SELECTOR



Sealing Joints in Hot Asphalt to Asphalt, Concrete and Steel	•	•
Flexible Watertight Seal	•	•
Polymer Modified Bitumen Strip	•	•
Fast Installation	•	•
Hand or Machine Applied	•	•
Hand Applied	•	•
Hot Applied	•	
Cold Applied		•
No Skilled Labor Required	•	•
Primer Available	•	•



Ver 2004.30

DENSO NORTH AMERICA

USA

9710 Telge Road Houston, Texas 77095 Tel: 281-821-3355 info@densona.com **CANADA**

90 Ironside Crescent, Unit 12 Toronto, Ontario M1X 1M3 Tel: 416-291-3435 sales@densona-ca.com

