PRODUCT DATA SHEET

Denso D14 Scrim

Saturation Fabric for Covercoat System

Description

Denso D14 Scrim is a non-woven fabric with longitudinal reinforcing stitching, manufactured from 100% polyester fibers.

Uses

Denso D14 Scrim is used as a reinforcement when saturated with Denso Basecoat[™] for the Denso Covercoat System[™].

Features

- · Can be easily saturated
- · Strong reinforcement fabric
- · Conforms to irregular shapes & profiles
- · Long shelf life

Application

The Denso D14 Scrim is cut into lengths and "dipped" into the mixed solution of Denso Basecoat, fully saturated in their trimmed states and applied over the Denso Hi-Tack™ Tape and pressed flat to relieve any trapped air pockets. The Denso D14 Scrim is further protected and reinforced by additional liberal amounts of Denso Basecoat. Allow the Denso Basecoat to cure for an additional 12 hours before applying Archco 15™.



Denso D14 Scrim[™]

Property Specifications		
Properties	English	METRIC
Thickness (ASTM D1000)	35 mils	900 μm
Weight	.020 lbs/ft2.	100 g/m² avg.
Breaking Strength (ASTM D1000)	1.24 lbf/in.	140 N/25mm minimum
Elongation @ Break	25% average	25% average
Roll Widths	4" and 6"	100 and 150 mm
Roll Length	66 ft	20 m

PACKAGING:

4" (100 mm) x 66' (20 m) x 9 rolls / case 6" (150 mm) x 66' (20 m) x 6 rolls / case

STORAGE: Store in original packaging in a cool, dry place away from any sources of ignition.

HEALTH AND SAFETY: Normal hygiene procedures. Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating. See safety data sheet for further information.



DENSO NORTH AMERICA

HOUSTON: 9710 Telge Road, Houston, Texas, U.S.A. 77095 Tel: 281-821-3355 Fax: 281-821-0304 TORONTO: 90 Ironside Crescent, Unit 12, Toronto, Ontario, Canada M1X1M3 Tel: 416-291-3435 Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.