

ARCHCO™ CORROSION RESISTANT LININGS

PROTECTIVE LININGS FOR PIPES

LININGS FOR:

Chemical Resistance

Abrasion Resistance


Heat Resistance up to 400°F (203°C) and Spikes up to 450°F (232°C)

Internal Steel Substrates

Internal Steel Pipe Surface

Wide Range of Temperatures & Pressures





ARCHCO™ 453 EPOXY

Two-part epoxy for industrial storage and process tanks and pipelines.



ARCHCO™ 453HT EPOXY

Internal epoxy phenolic-novolac lining for tanks and pipes.

Archco™ Linings and coatings are designed specifically to protect Crude, Gas & Diesel Tanks, Ethanol Tanks, Petrochemical Tanks, Heat Exchangers, Knock Out Drums, Chime Areas, Bund Areas, Pressure Vessels and Internal Pipes & Valves.



ARCHCO™ 453HTP EPOXY

Abrasion resistant internal epoxy phenolic-novolac lining for pipes.



ARCHCO™ 466 EPOXY

Glass flake epoxy coating for high temperature and chemically aggressive environments.

FEATURES

- Excellent adhesion
- Very low permeability
- Excellent high temperature resistance (up to 400°F / 203°C)
- Outstanding abrasion resistance
- Excellent resistance to H₂S gases
- Excellent chemical resistance
- Excellent cathodic disbondment resistance
- Suitable for fresh and salt water immersion
- Excellent flexibility
- MIC & acid resistance
- Resistance to hydrocarbons
- Long working life

Ver 2407.02



DENSO NORTH AMERICA

USA 9710 Telge Road Houston, Texas 77095 Tel: 281-821-3355 info@densona.com CANADA
90 Ironside Crescent, Unit 12
Toronto, Ontario M1X 1M3
Tel: 416-291-3435
sales@densona-ca.com

